



Flanges	øD	øk	ød	Number of Holes
DN 32	5.5118	3.937	0.7087	4
DN 40	5.9055	4.3307	0.7087	4
DN 50	6.4961	4.9213	0.7087	4
DN 65	7.2835	5.7087	0.7087	4
DN 80	7.874	6.2992	0.7087	8

CBF Pump Model appx. 2900 rpm.	Threephase Motor				Flanges		Dimensions of pump						Pump with footing					Net weight ≈ lbs.	Inches
	265V kW	230V kW	460V kW	400V kW	≈ L	≈ M	DN _S	DN _D	A	B	C	G	H	R	X	g	m		
CBF 32-160	1.5	1.5	10.55	4.88	1.97	1.26	3.15	5.51	2.76	6.29	5.2	10	4.33	4.65	9.45	7.48	.748	6.97	54
	2.2	2.2	11.54	4.88	1.97	1.26	3.15	5.51	2.76	6.29	5.2	10	4.33	4.65	9.45	7.48	.748	6.97	60.63
CBF 50-125	3.0	3.0	13.03	4.88	1.97	1.26	3.15	5.59	2.76	6.29	6.29	11.65	4.33	4.65	9.45	7.48	.787	7.91	77.16
	4.0	4.0	13.94	5.55	1.97	1.26	3.15	5.59	2.76	6.29	6.29	11.65	4.33	4.65	9.45	7.48	.787	7.91	93.7

CBF

Motor: 60Hz
 Attention: actual motor dimensions possible may differ from the drawing.
 Subject to alteration! ANSI Companion flanges available upon request

Compact Stainless Vortex Pump

Shanley Pump
& Equipment, Inc.

