




DIMENSIONS "TECNIUM" PUMP TYPE:

BNB
65-250



	PUMP	BASE PLATE	MOTOR	FLANGES	SPEED RATING/r.p.m.
STANDARD	DIN EN 22858 ISO 2858 NF E 44121	EN 23661 ISO 3661	NEMA-IP 55	ANSI 150 lbs.	$\frac{1.450}{1.740}$



Pump type	Motor	Pump		Assembly								Base plate					
	Tipo HP	a	f	h1	h2	H	L1	A	B2	k	k1	x	L3	L2	B3	B1	d
BNB 65-250	10	4.92	19.69	7.87	9.84	10.9	44.1	3.54	19.3	20.67	50.79	5.51	29.13	7.5	17.32	14.96	0.91

Df	Sf	Discharge Df	Suction Sf
DN 2-1/2"	4"		
D 7"	9"		
C 5.5"	7.5"		
U 4.28"	6.19"		
N" 4	8		
S 5/8"	5/8"		
L 1.97"	2.17"		

Coupling } A2

ITEM _____

ORDER N: _____

CLIENT: _____

Loads in nozzles

Traction $\frac{Df 2 \frac{1}{2}}{Sf 4} = \frac{360}{585} \text{ lb.}$

Moment $\frac{Df 2 \frac{1}{2}}{Sf 3} = \frac{12765}{14965} \text{ lb.in}$

Weight (lbs.)

Pump	Base plate	Motor
222.2	121	121

Dimensions in inches

Ed. 05.07

TECNIUM®

Tech. Sheet
49122